TECHNICAL SPECIFICATION

hushfree.XM HUS-AP-006

FOR COMFORTABLE TEAMWORK AND MEETINGS FOR 1 TO 2 PEOPLE

HushFree.XM is an B-rated acoustic booth with new 500 lux lighting. The booth is designed for face-to-face and hybrid meetings, important conversations requiring confidentiality or creative work. You can equip the booth as you wish – arrange the interior yourself. The booth can be equipped with a ready-made table and two sofas. HushFree.XM lets you hold meetings of up to two people in comfort.

DIMENSIONING

1-2

W/D/H: exterior 2210 x 900 x 2300 mm
interior 1993 x 820 x 2034 mm

Weight: 501 kg **Weight with box:** 617 kg

Logistic data is available on request.





1 Access to power cable







LIGHTING

LED ceiling light 30 W / 4000 K, lm – 2300; lux – min. 300 / medium 500 / max. 700.
Adjusted in the range of 2200-6500K with hushAssistant option.

TECHNICAL SPECIFICATION

hushfree.XM HUS-AP-006

ELECTRIC SYSTEM

LED CEILING LIGHT x2.

POWER SUPPLY MODULE (basic): 2x power supply 230V, 2 x RJ45.

POWER SUPPLY MODULE (optional, as required): type A charger, 1x type C charger with a total power 25W MAX.

POWER CABLE: black – access from the floor with 5000 mm overall length. Access from the booth exit, 3400 mm.

LAN PLUG CAT.6: available with 5000 mm total cable length, and available with 3400 mm at the booth exit.

MOTION SENSOR: located on the middle column, activates lighting at 50% and ventilation systems at 100% of total power. Standby power consumption 5 W.

Maximum power consumption of the product 0,28A – 64,5W.

VENTILATION SYSTEM

4 fans x 80 m^3/h* / 75 seconds**.



* maximum performance of the single fan, taking into account losses in the ventilation system.
** total time of air change inside based on the volume and capacity of one fan.

EXTERIOR

GLASS DOOR WITH LATCH HANDLE: acoustic, tempered and laminated safety glass 10 mm, 5.5.2 thickness, including the 5 mm glass, 2 mm acoustic sheet and 5 mm glass. Anti-collision marking – silkscreen integrated inside the 65 mm wide glass. Transparent glass.

REAR SIDE GLASS PANELS: acoustic and laminated glass 10 mm (RW= 34 dB), 5.5.2 thickness, including the 5 mm glass, 2 mm acoustic sheet and 5 mm glass. Placed in aluminum profiles with acoustic seal. Transparent glass. Matte version as an option.

DOOR HANDLE AND HINGES: painted in cosmos grey. Handle dimensions: 45 x 221 mm.

CASE: 3-layer honeycomb board with a thickness of 38 mm. Both sides covered with melamine and finished with ABS edging. Structure prepared for anti-seismic ground fixing.

8 integrated castors with levelling feet.

INTERIOR

INTEGRAL CARPETED FLOOR: complies with ASTM D2859 – 16 (2021), standard test method for ignitability characteristics of ready to use textile floor covering materials. Adapted to commercial intensive use (hotel room, hotel suite, boutique, shop, restaurant, conference room, high traffic office, reception, stairs). Graphite color.

PANEL WITH CEILING LIGHT: in cosmos grey. Total dimensions 190 x 640 mm, ceiling light dimensions: 70 x 640 mm, hole prepared for smoke detector diameter 20 mm, hole prepared for sprinkler installation diameter 65 mm.

KNOBS AND ELECTRICAL PLUGS DIAMETER (standard):
Knob – 69 mm. Plug – 94 mm.

INTERIOR PANELS: Made as a composite based on PETFELT, polyester fleece and fabric. PUR fire-retardant foam with acoustic properties, re-bonded.

UPHOLSTERY Athlon Plus:
weight: 750 g/lm; **composition:** 56% polyester, 44% Trevira CS; **flammability:** cigarette (BS EN 1021-1), cigarettes and matches (BS EN 1021 1&2), CA TB 117-2013; **light fastness:** 5 (EN ISO 105BO2); **pilling resistance:** 5 (EN ISO 12945-2); **abrasion resistance:** 100.000 martindale cycles (EN ISO 12947-2); **certification:** OEKO-TEX® STANDARD 100.

TABLE (optional): measuring W/D/H 769 x 510 x 735 mm. Made of 18 mm thick plywood covered with HPL laminate on both sides. Support leg made of 30 x 50 mm steel profile, powder-coated in cosmos grey colour.
Maximum load – **15 kg**.

BOOTH OCCUPANCY INDICATOR (optional): booth occupancy light indicator, measuring 96 x 96 x 38 mm, prepared to be integrated with the ventilation module power supply. Adapted to be positioned on the booth ceiling anywhere within 1000 mm of the fan housing. Actuated by a motion sensor.

HUSHBOOKING (optional): measuring 114 x 22.5 x 192 mm. Luminous side panel and touchscreen display indicating booth occupancy, enabling reservations, prepared to be integrated with the booth's power supply. The system can be integrated with the Microsoft 365 platform.

HUSHASSISTANT (optional): 4-inch, high-resolution round touchscreen for adjusting lighting and airflow. HushAssistant can adjust the brightness and color of the lighting and activate modes for various needs. Enables reservation, prepared to be integrated with the pod power supply. The system supports integration with the Microsoft 365 platform.

SET OF SOFAS (optional): seat module including backrest, available in left and right versions of 750 x 534 x 688 mm overall dimensions. Seat height – 473 mm, backrest height from seat – 215 mm. Inner structure made of wood-based materials, sprung layer – 100% PU foam, fluffy fleece 100% Polyester. Outer layer – upholstery fabric. Maximum load of the sofa – 150 kg.

TECHNICAL SPECIFICATION

hushfree.XM HUS-AP-006

OPTIONAL EQUIPMENT	WEIGHT	WEIGHT WITH BOX
SOFA (1 pc.)	16 kg	17 kg
TABLE HUSHFREE.XM	9 kg	10 kg

ACOUSTIC RATING

Acoustic measurements according to ISO 23351-1:2020 – $D_{s,A}$ = 28,7 dB class B.

SUSTAINABLE DEVELOPMENT

Hushoffice booths are manufactured in the ISO 9001 and 14001 certified production factory in Poland by Mikomax Smart Office. The production process complies with the ISO 14001 environmental management system standard. Hushoffice booths are packaged and delivered in lightweight, recyclable cardboard boxes.

CERTIFICATION

5 JAHRE Garantie

Hergestellt in der EU

PEFC/04-04-0007
DINC-PEFC-COC-001290

hushoffice

Manufacturer: Fabryka Mebli Biurowych Mikomax sp. z o.o. I 93-231 Łódź ul. Dostawcza 4, Polska
Distributor: Mikomax sp. z o.o. I 93-231 Łódź ul. Dostawcza 4, Polska